

# PRODUCT BULLETIN

CLEAR
VC, ABS & STYRENE PIPES &

MADE IN U.S.A.

C - 570

Low VOC CLEANER

#### **GENERAL DESCRIPTION:**

PRO-WELD C-570 low VOC emission, water-thin, solvent cleaner. It is specifically formulated to remove grease, oil and dirt from the bonding surfaces of PVC, CPVC, ABS and Styrene pipe and fittings.

#### **APPLICATION:**

PRO-WELD C-570is an all-purpose cleaner and can be used on all sizes, classes and schedules of PVC, CPVC, ABS and Styrene pipe and fittings. It must be used only as a cleaner, in conjunction with the appropriate primer and/or cement combination. PRO-WELD C-570can also be used as a brush cleaner.

#### **AVAILABILITY:**

This product is available in ¼ pint (118 ml), ½ pint (237 ml), pint (473 ml), quart (946 ml) and gallon (3.785 l) metal cans. For detailed information on containers and applicators, see our current Price List.

#### STANDARDS AND CERTIFICATION LISTINGS:

Meets SCAQMD Rule 1171.

### **SPECIFICATIONS:**

COLOR: Clear

SPECIFIC GRAVITY:  $0.794 \pm 0.04$ BROOKFIELD VISCOSITY: Water Thin

#### **DIRECTIONS FOR USE:**

- Before using this cleaner, pipe and fittings should be cut square, deburred and checked for proper fit.
- Use an applicator (e.g. dauber, brush top applicator or paintbrush) at least ½ the size of the pipe diameter. Do not use a rag as repeated contact of cleaner-infused rag with skin may cause irritation or blistering.
- Apply C-570 freely to the socket keeping surface wet and applicator wet and in motion for 5 15 seconds. Be sure to use a
  scrubbing motion to clean off all grease, oil and dirt. Re-dip if necessary. Avoid puddling the socket.
- Apply C-570 to the pipe surface in the same manner equal to the depth of the socket.
- Repeat application to the fitting socket.
- Allow C-570 to dry and then apply appropriate PRO-WELD primer and/or cement following instructions on the cans.

# **QUALITY ASSURANCE:**

PRO-WELD C-570 is carefully evaluated to assure that consistent high quality is maintained. Fourier transform infrared spectroscopy, gas chromatography, and additional in-depth testing ensures each batch is manufactured to exacting standards. A batch identification code is stamped on each can and assures traceability of all materials and processes used in manufacturing this product.

## **SPECIAL PRECAUTION:**

This product is intended for use by skilled individuals at their own risk. Installers should verify for themselves that they can make satisfactory joints under varying conditions. Detailed directions on making solvent cemented joints are printed on the container label. It is highly recommended that the installer review the instructions supplied by the pipe and fitting manufacturer.

Refer to the current PRO-WELD C-570Safety Data Sheet for additional safety precautions, first-aid, handling, storage and transportation information.

### **WARRANTY:**

MIGHTY PLUMBING SOLUTIONS ADHESIVES LLC. ("MPS"), warrants to all original purchasers of MPS products that all new MPS products shall be of good quality and free from defects in material and workmanship for the product's shelf life. If any MPS product becomes defective, or fails to conform to this written limited warranty under normal use and storage conditions, and if the original purchaser complies with the terms of this limited warranty, then MPS will, without charge, replace the nonconforming product.









# PRODUCT BULLETIN

C - 570

Low VOC CLEANER

This limited warranty shall extend to all products manufactured and sold by MPS. However, this limited warranty shall not extend to, nor shall MPS be responsible for, damages or loss resulting from accident, misuse, negligent use, improper application, or incorporation of MPS products into other products. In addition, any repackaging of MPS products also shall void the limited warranty provided herein.

Any defective MPS products shall be replaced pursuant to the terms of this limited warranty by returning the defective product, with transportation charges prepaid, to MPS at the following address:

227 Pine Meadow Court, North Brunswick, NJ 08902, U.S.A.

Any implied warranty in connection with any MPS product hereby is limited in duration to the period of this limited warranty. MPS shall not be responsible for, nor does this limited warranty extend to, consequential damage, or incidental damage or expense, including without limitation, injury to persons or property or loss of use. This limited warranty is in lieu of all other express warranties of MPS, and MPS does not assume, nor does it authorize any person to assume on its behalf, any other obligation or liability.



